

Direct Pumps and Tanks Ltd

Matrix Data Table

Dimensions, etc

PE	BOD/day kg	Flow/day M3	Length mm	Width mm	Depth mm	Std Inlet mm	Weight kg	Blower Rating
6	0.36	1.20	1500 diameter		2100	110	250	60 w
12	0.72	2.40	1900 diameter		2100	110	350	80 w
18	1.08	3.60	2500 diameter		2100	110	600	120 w
25	1.50	5.00	4710	1500	2174	160	1200	120 w
30	1.80	6.00	4010	2124	2174	160	1400	0.55 kw
40	2.40	8.00	5060	2124	2174	160	1700	0.55 kw
50	3.00	10.00	5610	2124	2174	160	1900	0.55 kw
60	3.60	12.00	6010	2124	2174	160	2100	0.75 kw
70	4.20	14.00	6810	2124	2174	160	2200	0.75 kw
80	4.80	16.00	6760	2524	2174	160	2300	0.75 kw
90	5.40	18.00	7360	2524	2174	160	2650	1.10 kw
100	6.00	20.00	7760	2524	2174	160	2900	1.10 kw
125	7.50	25.00	8200	1500	2900	160	3000	1.50 kw
150	9.00	30.00	9200	1500	2900	160	3250	1.50 kw
200	12.00	40.00	10500	1500	2900	160	3400	2.20 kw
250	15.00	50.00	11500	2250	2900	160	3600	2.20 kw
300	18.00	60.00	12000	2400	2900	160	3850	2.20 kw